



Four row tapered roller bearings



Designations	Boundary dimensions			
	d	D	B	T
	mm			
48680DW/48620/48620D	139.7	200.025	157.162	160.338
382930	150	210	165	165
381030X2		225	136	136
382034	170	260	230	230
381036X2	180	280	180	180
381040X2	200	310	200	200
382040		310	275	275
381041X2	205	320	205	205
382044	220	340	305	305
382048	240	360	310	310
382952/HC	260	360	265	265
381052X2		400	255	255
77752G		400	255	255
382052		400	345	345
77752		440	300	300



Boundary dimensions		Basic load ratings		Mass
r _{1,2} min	r _{3,4} min	Cr	Cor	
mm		kN		
1.1	1.8	535	1870	16.2
0.7	2.3	600	1590	21.2
3	2.5	540	1460	17.7
3	2.5	940	3100	43
3	2.5	835	2540	39.6
3	2.5	1970	1520	55.6
3	2.5	1230	4200	75.1
4	3.0	1060	2850	55.4
4	3.0	2290	5950	99.5
4	3.0	3300	2210	90.5
3	2.5	1730	5050	77.8
3.7	2.5	1480	4950	117
5	4.0	1910	4900	117
5	4.0	2850	7700	161
2	5.0	2670	5850	182